

KENT[®]
wood fires & heating



**LOVED HERE
SINCE 1979**



10 REASONS TO CHOOSE A KENT WOOD FIRE



WELCOME TO KENT

Kent wood fires offer more than heat; they have been adding comfort and atmosphere to New Zealand homes since 1979.

As a family owned company, we are committed to high standards and quality, so you can rest easy with a **15-year firebox warranty** on our indoor fire range. Designed in New Zealand for your New Zealand home, Kent indoor wood fires come to you backed by service and support.

Over 400,000 New Zealanders trust Kent to warm their home the way only a wood fire can. Join the Kent family and discover the range for yourself.

**LOVED HERE
SINCE 1979**



14kW WOOD FIRES



OXFORD WOOD FIRE. Pictured here with Kent floor protector.

Experience the comfort and reliability of our 14kW fireplaces. This range of compact fireplaces is perfectly sized to heat areas up to 150m², making them ideal for two or three bedroom homes. Enjoy cosy winter evenings in a warm, welcoming space that brings family and friends together. With three distinct base designs to choose from, the 14kW range offers a style to suit every home.

FEATURES

- Durable finish with high-temperature baked black paint.
- Excellent insulation and superior heat reflection from quality vermiculite bricks.
- Robust steel baffle plates for efficient double burn combustion.
- Sturdy steel plate top, perfect for boiling a kettle or cooking a winter favourite.

SPECIFICATIONS

- Average emission rate: **0.80g/kg**
- Overall average efficiency: **69%**
- ECAN Authorisation No:
Cardrona 165498
Oxford 165500
Benmore 165499

15 YEAR
FIREBOX WARRANTY

CARDRONA

KWF295-6960 | SKU 280583



MITRE 10 EXCLUSIVE

OXFORD

KWF295-6961 | SKU 280582



BENMORE

KWF295-6962 | SKU 280584




MITRE 10 EXCLUSIVE

INTERNAL FIREBOX

33L


W 479 X H 270 X D 350



INTERNAL FIREBOX

33L


W 479 X H 270 X D 350



INTERNAL FIREBOX

33L

W 479 X H 270 X D 350




14kW CLEARANCES


FREESTANDING		Minimum Installation Clearances With Flue Shield (mm)								Hearth Clearances (mm)				
Model	Model No.	A	B	C*	D	E	F	G	H	J	K	L	M	N
Cardrona	KWF295-6960	135	350	300	130	120	270	610	395	795	855	1140	585	1000
Oxford	KWF295-6961	135	350	300	130	120	270	610	395	795	855	1140	585	1000
Benmore	KWF295-6962	135	350	300	130	120	270	610	395	795	855	1140	585	1000

* Fuel loading opening to end of floor protector.

FREESTANDING WALL CLEARANCES



FREESTANDING CORNER CLEARANCES



18kW WOOD FIRES



HAAST WOOD FIRE. Pictured here with Kent floor protector.

The 18kW range is designed to heat spaces up to 210m², ideal for three or four bedroom homes. Set the scene for cosy winter evenings filled with comfort and good company. In three different base designs, as well as a benchtop option for custom installs, the 18kW range will have a design style to fit your home.


FEATURES

- Durable finish with high-temperature baked black paint.
- Excellent insulation and superior heat reflection from quality vermiculite bricks.
- Robust steel baffle plates for efficient double burn combustion.
- Sturdy steel plate top, perfect for boiling a kettle or cooking a winter favourite.
- For properties over 2 hectares: 18kw fireplaces can be fitted with a Rural Airslide, allowing for extended overnight burning - ideal for sustained heat output. Rural Airslide available separately (KWF299-7128).

SPECIFICATIONS

- Average emission rate: **0.98g/kg**
- Overall average efficiency: **66%**
- ECAN Authorisation No:
Haast 144660
Murchison 144662
Aspiring 144661
Forbes 181319

15 YEAR
FIREBOX WARRANTY



22kW
WOOD FIRE



RUAPEHU WOOD FIRE. Pictured here with Kent floor protector.

With an 83L firebox and a peak output of 22kW, the Ruapehu is the largest fireplace in our range. Built to heat homes up to 250m², it's ideal for spacious four-bedroom homes. An extra-wide window lets the fire take centre stage with a stunning panoramic flame view.

FEATURES

- Durable finish with high-temperature baked black paint.
- Excellent insulation and superior heat reflection from quality vermiculite bricks.
- Robust steel baffle plates for efficient double burn combustion.
- Sturdy steel plate top, perfect for boiling a kettle or cooking a winter favourite.
- For properties over 2 hectares: The Kent Ruapehu can be fitted with a Rural Airslide, allowing for extended overnight burning - ideal for sustained heat output. Rural Airslide available separately (KWF299-7241).

SPECIFICATIONS

- Average emission rate: **0.54g/kg**
- Overall average efficiency: **66%**
- ECAN Authorisation No: 191312


15 YEAR
FIREBOX WARRANTY

RUAPEHU

KWF295-6965 | SKU 2062828



INTERNAL FIREBOX
83L
W 640 X H 315 X D 415




22kW CLEARANCES


FREESTANDING		Minimum Installation Clearances With Flue Shield (mm)								Hearth Clearances (mm)				
Model	Model No.	A	B	C*	D	E	F	G	H	J	K	L	M	N
Ruapehu	KWF295-6965	150	200	300	100	170	315	580	540	960	913	1375	640	1180

* Fuel loading opening to end of floor protector.

FREESTANDING WALL CLEARANCES



FREESTANDING CORNER CLEARANCES



15kW INBUILT WOOD FIRES



190m²



RATA WOOD FIRE.

Indulge in the warmth and trusted performance of our elegant 15kW inbuilt fireplace range. Designed to efficiently heat up to 190m², they are ideal for two or three bedroom homes, delivering steady warmth throughout your living spaces. Inbuilt fireplaces save on floor space to create a clean, streamlined look that blends effortlessly into both modern and traditional interiors.

FEATURES

- Durable finish with high-temperature baked black paint.
- Strong construction built for lasting performance, backed by a 15-year firebox warranty.
- Vermiculite brick-lined firebox for excellent insulation and superior heat reflection.
- Multi-burn firebox helps keep the glass clear for an uninterrupted view of the flames.
- For properties over 2 hectares: The Kent Inbuilt range can be fitted with a Rural Airslide, allowing for extended overnight burning - ideal for sustained heat output. Rural Airslide available separately (KWF299-7127).

SPECIFICATIONS

- Average emission rate: **0.51g/kg**
- Overall average efficiency: **69%**
- ECAN Authorisation No:

Rata	142831
Logfire II	142832

15 YEAR
FIREBOX WARRANTY

RATA

KWF295-6938 | SKU 243258



LOGFIRE II




KWF295-6937 | SKU 280589



INTERNAL FIREBOX

41L




W 380 X H 280 X D 400



INTERNAL FIREBOX

41L

W 479 X H 270 X D 350





15kW CLEARANCES

INBUILT		Minimum Installation Clearances (mm)								Maximum Mantle Projection (mm)
Model	Model No.	A	B	C*	D	E	F**	G	H	I
Rata	KWF295-6938	25	500	300	200	840	59	2000	1200	160
Logfire II	KWF295-6937	25	500	300	200	840	59	2000	1200	160

* Floor protector from front of fascia. ** Heat sensitive floors only. Refer installation instructions for other floor types.

INBUILT CLEARANCES



TEKAPO OUTDOOR WOOD FIRE



TEKAPO WOOD FIRE. Pictured here with trolley base.



ASADO BBQ KIT. Available separately.



PIZZA STONES. Included.

In four stylish designs to enhance your outdoor space, the Tekapo is perfect for creating a cosy outdoor gathering spot for family and friends. Use it as an outdoor fire or enjoy wood-fired pizzas with the integrated pizza oven. For even greater versatility, the optional Asado BBQ Kit adds a grill, hotplate, and a charcoal burn box. Combining dependable performance with a sleek, modern aesthetic, the Tekapo transforms any outdoor area into a warm and inviting retreat.

FEATURES

- Integrated pizza oven delivers authentic wood-fired pizza results.
- Durable steel fire grate provides strong, long-lasting support during every burn.
- Fire bricks included for superior heat retention and efficient, even heating.
- A magnetic stainless steel door keeps the firebox sealed when not in use.
- Complete flue kit supplied to ensure safe and effective smoke ventilation.
- Optional Asado BBQ kit available to enhance versatility and expand your outdoor cooking experience (KWF298-7400 available separately).

SPECIFICATIONS

- 4mm matt black mild steel
- 30mm refractory bricks
- 2 x pizza stones included
- 10mm heavy-duty steel fire grate
- 1200 H X 200 D flue kit included
- Wind directional cowl

TEKAPO WITH TROLLEY BASE KWF292-5911



DIMENSIONS
W 1000 X H 1810 X D 460 (mm)

WEIGHT
317KG

TEKAPO FREESTANDING KWF292-5914



DIMENSIONS
W 950 X H 1515 X D 460 (mm)

WEIGHT
282KG

TEKAPO BENCHTOP KWF292-5905



DIMENSIONS
W 950 X H 1150 X D 460 (mm)

WEIGHT
247KG

TEKAPO INBUILT KWF292-5904



DIMENSIONS
W 950 X H 775 X D 460 (mm)

WEIGHT
245.5KG

TEKAPO CLEARANCES


OUTDOOR FIRES

Model	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
Tekapo	1200	1200	1000	1000	1200	1484	1680	1340	1475	1000	1190	700	175	470	1250


Freestanding Minimum Installation Clearances (mm)

Inbuilt Minimum Installation Clearances (mm)


FREESTANDING WALL CLEARANCES



FREESTANDING CORNER CLEARANCES



INBUILT CLEARANCES



INBUILT INSTRUCTIONS



TEKAPO ASADO BBQ KIT KWF298-7400



Enhance your Kent Tekapo Outdoor Fire with the Asado BBQ Kit, turning your Tekapo into a full wood-fired cooking experience. The kit includes an upgraded hot plate and reinforced grill holder for added stability, plus a charcoal burn box for precise heat control. A deep dish mild-steel hot plate ensures even heat distribution, while the large stainless steel grill offers plenty of cooking space, perfect for effortless outdoor entertaining.

FLOOR PROTECTORS

FEATURES


- Perfect for both wall and corner installation
- Constructed in 3mm steel
- Black powder-coated finish
- Suits a majority of freestanding wood fires

RECOMMENDED FLOOR PROTECTORS FOR KENT WOOD FIRES:

Model No.	Location	Size	CARDRONA	BENMORE	OXFORD	HAAST	ASPIRING	MURCHISON	RUAPEHU
KWF298-7048	Wall	Small	*	*	*				
KWF298-7049	Wall	Large	*	*	*	*	*	*	*
KWF298-7050	Corner	Small	*	*	*				
KWF298-7051	Corner	Large	*	*	*	*	*	*	
KWF298-7127	Corner	X-Large	*	*	*	*	*	*	*

Note: This product is an ash protector, it is not an insulated protector.
Kent floor protectors meet minimum floor protection requirements AS/NZS2918:2001.

DIMENSIONS (mm):



MOISTURE GAUGE

KWF298-7004

Firewood with less than 25% moisture content* will burn cleaner, provide maximum heat outputs, reduce fuel costs and help keep fires and flues performing properly.

SPECIFICATIONS

- Simple to use, with digital bar-graph display
- Accurate readings, with low 0.1% error margin
- Senses a maximum of 40% moisture content
- Low battery use, with auto-switch-off function
- Four sensor prongs for reliable readings
- Includes handy canvas bag and 9V battery




* By wet weight ratio

WOOD FIRE FLUE KITS

Kent wood fires are sold without a flue. New Zealand designed Inbuilt and Freestanding flue kits are available for your chosen wood fire installation. Each flue kit contains the parts required for a standard installation. Your dealer/installer will be able to assist you with your requirements.

FREESTANDING WOOD FIRES HAVE TWO FLUE KIT OPTIONS AVAILABLE:

- All Kent freestanding flues have a triple skin design (an inner flue and outer flue casings). The inner flue allows all of the smoke to exit the fire cleanly. The outer casings provide thermal insulation and allow air to flow between them and the inner flue which insulates the inner flue when the fire is running.
- In the standard Freestanding Flue Kit, air from within the room where the fire is located enters the space between the liners and the main flue via the gap between the ceiling and the ceiling plate. This will allow some of the warm air generated by the fire burning to escape up the gap between the flue casings.



FREESTANDING FLUE KITS: Standard Flue: KWF298-7404

INBUILT WOOD FIRES HAVE TWO FLUE KIT OPTIONS AVAILABLE:

- The standard Inbuilt Flue Kit is designed to be installed in an existing masonry chimney.
- The Zero Clearance Kit provides an insulated surround for the Rata and Logfire II fires to allow them to be installed in a non-masonry chimney breast. The Zero Clearance Kit comprises a steel insulation box which provides thermal clearance to combustible materials and a flue transition adaptor.

Standard Flue: For masonry installation KWF298-6025	Zero Clearance Box & 600mm Transition (Flue Kit not included): KWF298-7371	Zero Clearance Box & 600mm Transition (3.6m Flue Kit included): KWF298-7374
---	--	---

All Kent flue kits are tested to AS/NZS2918:2001 Appendix F.

5 STEP PRE-PURCHASE GUIDE

1.

CHECK FOR LOCAL COUNCIL BY-LAWS

- National Environmental Standards permit a maximum of 1.5 grams of particles per 1 kilogram of dry wood burnt. However some councils have stricter airshed requirements.
- Wood fire heating efficiencies must be greater than 65%.

2.

CORRECTLY SIZE YOUR FIRE

- Determine the area you wish to heat, and calculate how many square metres this covers.
- Compare your area with the heating area specification.
- We base our calculations on a nominal 'stud' (ceiling) height of 2.4m and make the assumption the insulation of the property is up to current standards.
- If you have a taller stud height or the insulation in your property needs upgrading you may require more heating capacity.

3.

CHECK YOUR LAND AREA

- **For properties under 2 hectares:** A clean-air approved wood fire is recommended to meet local council requirements and ensure optimal environmental performance
- **For properties over 2 hectares:** Fires from our range can be fitted with a Rural Airslide, converting them for non-clean air use in rural applications. This allows for extended overnight burning, ideal for sustained heat output.

4.

CONSIDER YOUR FIRE LOCATION

- Wood fires can be inbuilt or freestanding.
- Fires are positioned for best flue installation.
- The position of your fire affects how well it can heat your whole home.

5.

CHECK YOUR INSTALLER IS APPROVED

- Wood fires should always be installed by an approved installer.
- We suggest using a NZHHA approved installer as they will also help manage the council permit process.
- The installer should visit your home and advise on the best fire size, type and location.